



4 way satellite splitter

for the 4-fold distribution of Sat signals

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588223110	silver	0022/3111	114 g	100 g	8.50 x 5.50 x 1.80 cm	9.00 x 10.00 x 2.50 cm

TOP FEATURES

DC power pass

diode decoupled

DiSEqC-compatible

TECHNIROUTER-compatible

DECOUPLING

5 - 862 MHz : Typ. 20 dB

950 - 1750 MHz : Typ. 20 dB

1750 - 2150 MHz : Typ. 20 dB

RETURN LOSS

5 - 862 MHz : Typ. 12 dB

950 - 1750 MHz : Typ. 10 dB

1750 - 2150 MHz : Typ. 10 dB

TECHNICAL DATA

Input : 1

Outputs : 4

Frequency range : 5 ... 2400 MHz

Shielding factor : ≥ 75 dB EN 50083-2 (Class A)

Connector type : F female

Impedance : 75 Ω

TRANSMISSION LOSS

5 - 862 MHz : Typ. 8 dB (± 1)

950 - 1750 MHz : Typ. 8 dB (± 1)

1750 - 2150 MHz : Typ. 9 dB (± 1)