



# Delock Cable HDMI-A male > HDMI-A female panel-mount 4K 30 Hz 2 m

## Description

This cable by Delock can be used to extend an HDMI connection and to connect various devices. The female port can be attached with two screws, e.g. to a slot bracket, a cable duct or an enclosure with the corresponding opening. In this way, it is possible to install a HDMI connector in an easily accessible position.



ca. 2 m

## Specification

- Connectors:
  - 1 x HDMI-A 19 pin male >
  - 1 x HDMI-A 19 pin female panel-mount
- High Speed HDMI with Ethernet (HEC) specification
- Screw type: #4-40 UNC
- Mounting hole: ca. 15 x 6 mm, screw hole pitch ca. 30 mm
- Cable gauge: 28 AWG
- Cable diameter: ca. 7.3 mm
- Gold-plated connectors
- Transfer of audio and video signals
- Data transfer rate up to 10.2 Gb/s
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- 3D support up to 1080p in two video streams with each 60 pictures per second
- Supports Dolby® TrueHD and DTS-HD Master Audio™
- Colour: black
- Length incl. connectors: ca. 2.0 m

## System requirements

- A free HDMI interface

## Package content

- HDMI panel-mount cable
- 2 screws

## Item no. 85464

EAN: 4043619854646

Country of origin: China

Package: Poly bag



## Images





|                            |                                     |
|----------------------------|-------------------------------------|
| General                    |                                     |
| Specification:             | High Speed HDMI with Ethernet       |
| Interface                  |                                     |
| connector 1:               | 1 x High Speed HDMI-A 19 pin male   |
| connector 2:               | 1 x High Speed HDMI-A 19 pin female |
| Technical characteristics  |                                     |
| Data transfer rate:        | 10.2 Gb/s                           |
| Maximum screen resolution: | 3840 x 2160 @ 30 Hz                 |
| Physical characteristics   |                                     |
| Cable diameter:            | 7.3 mm                              |
| Pin finishing:             | gold-plated                         |
| Conductor gauge:           | 28 AWG                              |
| Screw distance:            | 30 mm                               |
| Screw type:                | #4-40 UNC                           |
| Length:                    | 2 m                                 |
| Colour:                    | black                               |